


Sending card

DS802D

V1.1

Jan 2018

1. Features



DS802 is for **double/single** color led screen, and it has the following features:

- 1) One DVI video signal input;
- 2) One Audio signal input;
- 3) Set via USB; can be cascaded to drive a larger screen, up to 4 cards cascaded;

Official website: www.linsn.com

Add: Floor 15&16, Jiajiahao Business Building, No. 10168, Shennan Blvd,
Nanshan District, Shenzhen

Tel: +86-0755-86183590/ 4008836968

- 4) Two network outputs; single port maximum support 655360 pixels;
- 5) Support adjusting brightness manually (requires working with outer box); three scales can be set: 16-grade, 32-grade and 64-grade;
- 6) Support 60Hz and 30Hz output mode.

2.Capacity

60Hz mode (using two ports)	30Hz mode (using two ports)
2048 × 640	4032 × 512
1920 × 672	3840 × 544
1792 × 720	3584 × 576
1600 × 800	3392 × 608
1472 × 880	3200 × 640
1344 × 960	3072 × 672
1280 × 1024	2880 × 704
1024 × 1280 (require supporting by graphics card)	2560 × 800
832 × 1280 (require supporting by graphics card)	2368 × 864
640 × 1280 (require	2048 × 1024

Official website: www.linsn.com

Add: Floor 15&16, Jiajahao Business Building, No. 10168, Shennan Blvd,
Nanshan District, Shenzhen

Tel: +86-0755-86183590/ 4008836968

supporting by graphics card)	
-------------------------------	--

3.Working conditions

Rated voltage (V)	5	maximu m	5.5	minimu m	4.5
Rated current (A)	0.50	maximu m	0.57	minimu m	0.46
Rated power consumption (W)	2.5	maximu m	3.1	minimu m	2.1
Working temperature (°C)	-20°C ~ 70°C				
Working humidity (%)	0% ~ 95%				

END

Official website: www.linsn.com

Add: Floor 15&16, Jiajiahao Business Building, No. 10168, Shennan Blvd,
Nanshan District, Shenzhen

Tel: +86-0755-86183590/ 4008836968